

Notes:

- All nail fixings pre-drilled minimum 1mm diameter smaller than nail gauge
- All products to be pre-coated & cut edges to be sealed as per Branz Bulletin 411
- All materials and fixtures are to comply with E2/AS1 clause 2.2
- Provide PVC tape bond break between H3.2 battens and any flashing
- Vertical Shiplap profiles to be fixed with a minimum 2mm gap at the overlap between boards
- Rigid & Flexible underlay as per Table 23 and Clauses 9.1.5 to 9.1.7 E2/AS1.
- Timber to NZBC B2 Durability b23.1 (b) Western Red Cedar, Larch

Framing

Flashing tape over Z flashing
with PBS Butyl tapeCCA treated H3.2 45x20mm
BBS "H" timber cavity batten.
Horizontal @ 480mm max centresVentclad cavity closer with
vent slots15mm
Expansion gap

50 min

Horizontal Z flashing
Back flash internal
& external joints with
seal edge

32.21 min

Building wrap as per E2/AS1
table 23BBS Vertical Shiplap
Weatherboard75mm annular grooved rose head,
silicone bronze or stainless steel nails

TITLE:

NAME

SIGNATURE

DATE

DRAWN

CHK'D

APPV'D



Horizontal Joint Detail

DWG NO.

V-CW-13

A4

SCALE: 1:10 DNS SHEET 1 OF 1