

Auckland

82 Henderson Valley Rd Henderson P 09 8360124 f 09 8360103 e - auck@bbstimbers.co.nz

Whangarei

27 Kioreroa Rd Whangarei p 09 4389358 f 09 4300455 e- office@bbstimbers.co.nz

Christchurch

14 Halwyn Drive Hei Hei p 03 3445591 f 03 3445592 e- chch@bbstimbers.co.nz

Ash (American)

Specification sheet



Other Name(s): White Ash

Scientific Name: Fraxinus americana

Distribution: North America

Average Dried Weight: 670 kg/M3

Durability: None Durable

Janka Hardness: (5.6 kN)

Modulus of Rupture/Bending

Strength (100 MPa)

Modulus of Elasticity/ stiffness: (11.9 GPa)

Strength: SD5

AMERICAN WHITE ASH

Seasoning:

Dries well with little degrade.

Characteristics:

- The sapwood and heartwood are almost white to beige with the heartwood having incidences of dark beige to brown features on occasions.
- Well figured with good strength, elasticity, toughness, stiffness and hardness allied to its light weight.

Working Qualities:

Machines reasonably well. Good staining and polishing qualities.

Uses

High class joinery, boat interiors, musical instruments and striking tool handles.

Product Attributes:

- Generally cream to white.
- Machines well.
- Good strength and toughness / weight ratio.
- Veneers available.
- Strong grain figure.
- Flat sawn.
- Good polishing and staining qualities.

Product Limitations

- Can have brown heart.
- Seldom available over 3.3m in length.
- No fixed widths.