

Hardwood Decking Species Guide

Technical Specifications

	GARAPA	PURPLEHEART	KWILA	CUMARU
				
Density –KG/M3 (dry)	850	870	870	1085
Durability	Class 2 (Durable) above ground	Class 1 (Very Durable) above ground	Class 2 (Durable) above ground	Class 1 (Very Durable) above ground
Stability	3.5% Radial - 6.5% Tangential	3.0% Radial - 6.0% Tangential	1.5% Radial - 2.5% Tangential	
Standard sizes	90x19 , 140x19/21	90x19 , 140x19, 140x21 Camber deck Profile	140x19	140X21
Length Spread	1.8 - 5.7m 3.0m average	1.2 - 5.4m 3.0m average	1.8 - 5.7m 3.0m average	1.8 - 5.4m 3.0m average
Sustainability/ certified	FSC certified on request	FSC certified on request	FSC certified	VLO Certified
Tannin Bleed	Colour Golden - Minimal Bleed	Colour Purple - Minimal Bleed	Colour Brown - Heavy Bleed	Colour Brown - Minimal Bleed
Surface checking	May occur over time	May occur over time	May occur over time	May occur over time
Black Spotting	Can occur on site with contamination Can be cleaned with Deck cleaners	Can occur with metal filings on site Can be cleaned with Deck cleaners	Can occur on site with contamination Can be cleaned with Deck cleaners	Can occur on site with contamination Can be cleaned with Deck cleaners
Weathered colour	Silver/ Grey	Silver/ Grey	Silver/ Grey	Silver/ Grey



All decking can be BBS factory coated with Dryden deck oil by volume.
See manufacturers application information at— www.woodoil.co.nz

office@bbstimbers.co.nz

bbstimbers.co.nz

Whangarei

27 Kioreroa Road, Whangarei
PO Box 1407

Ph 094389358

f 094300455

Auckland

82 Henderson Valley
Road, Henderson

Ph 098360124

f 098360103

Christchurch

14 Halwyn Drive
Hei Hei

Ph 033445591

f 033445592